

## Camera G4 Pro



## Mechanical

Dimensions	Ø 86 x 153 mm (Ø 3.39 x 6.02")
Weight	700 g (1.54 lb)
Enclosure materials	Polycarbonate, aluminum alloy
Mounting material	Aluminum alloy
Weatherproofing	IP67

## Optics

Sensor	1/2" 8MP sensor
Lens	F 4.1 - 12.3 mm; <i>f</i> /1.53 - <i>f</i> /3.3
View angle	Wide: H 110°, V 60°, D 128° Zoom: H 40°, V 20°, D 40°
Night mode	Built-in IR LED illumination and IR cut filter

## Video

Video compression	H.264
Resolution	3840 x 2160 (16:9)
Maximum frame rate	50 FPS
Image settings	Flip, brightness, contrast, 50/60 Hz flicker reduction, WDR, hue, infrared, sharpness, saturation, denoise

## System

Management interface	UniFi Protect
Networking interface	GbE RJ45 port
Max. power consumption	12.5W
Power method	802.3af PoE mode A
Button	Factory reset
Mounting	Wall/ceiling/pole (kit included)
Operating temperature	-20 to 50° C (-4 to 122° F)
Operating humidity	0 to 90% noncondensing
Certifications	FCC, IC, CE

## Audio

Microphone	Yes (can be disabled in software)
------------	-----------------------------------

## Software

UniFi OS application	UniFi Protect
Mobile apps	UniFi Protect iOS and Android



Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at: [www.ui.com/support/warranty](http://www.ui.com/support/warranty)

©2020 Ubiquiti Inc. All rights reserved. Ubiquiti, Ubiquiti Networks, the Ubiquiti U logo, the Ubiquiti beam logo, UniFi, and UniFi Protect are trademarks or registered trademarks of Ubiquiti Inc. in the United States and in other countries. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple, Inc., registered in the U.S. and other countries. Android, Google, Google Play, the Google Play logo and other marks are trademarks of Google LLC. All other trademarks are the property of their respective owners.